NSN 5905-00-122-8576

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-122-8576

Section Quantity:

Section Quantity: Body Style: Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.957 inches First Flat Length: 0.625 inches Flat Height: Between 0.211 inches and 0.221 inches **Body Diameter:** 1.680 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** Between 1.453 inches and 1.547 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.410 inches **Overall Diameter:** 2.260 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Maximum Starting Torque:** 40.00 inch-ounces **Maximum Stop Torque:** 240.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.485 inches and 0.515 inches **Screw Thread Diameter:**

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

NSN 5905-00-122-8576

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 275.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
25.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No