NSN 5905-00-122-8618

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-122-8618

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.969 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.438 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally closed
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
250.0 ohms single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section

-10.0 to 10.0 single section

Resistance Tolerance Per Section In Percent:

NSN 5905-00-122-8618

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
F single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:

Demilitarization:

Unit Of Measure:

No

N/a

Fiig:

A002a0