

View Online at <https://aerobasegroup.com/nsn/5905-00-123-0826>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.266 inches

**Body Diameter:**

0.922 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.125 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

1.141 inches

**Undercut Diameter:**

0.125 inches

**Shaft Style:**

Round, stepped

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

300.0

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.438 inches

**Fragility Factor:**

Moderately delicate

**Undercut Length:**

0.750 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

1.000 megohms 2nd section

**Rotary Actuator Travel In Angular Deg:**

300.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 all sections

**Power Dissipation Rating Per Section In Watts:**

0.333 free air all sections

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0