NSN 5905-00-124-0053

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-124-0053 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.535 inches **Overall Height:** Between 0.490 inches and 0.510 inches **Overall Width:** Between 0.182 inches and 0.192 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches **Shaft Diameter:** Between 0.065 inches and 0.095 inches **Shaft Length:** Between 0.025 inches and 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.182 inches and 0.192 inches **Body Height:** Between 0.490 inches and 0.510 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.515 inches and 0.530 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Electrical Resistance Per Section:**

Mounting Method:
Unthreaded hole
Electrical Resistance Per
20.0 ohms single section

NSN 5905-00-124-0053

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: