NSN 5905-00-124-5025

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-124-5025

Electrical Resistance: 29:100 kilohms Resistance Tolerance in Percent: 0.500 to 0.500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Interpurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Inclosure Method: Incapsulated Ferminal Type: Wife lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avial terminals one end Test Data Document: 13:498-mili33 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 0.500 to 0.500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Tempurature Range Of Tempur	-20.0 to 20.0
Resistance Tolerance in Percent: 0.500 to 0.500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0 to 145.0 notosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Avaid terminals one end Test Data Document: 131349-milira3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Inclosure Method: Incapsulated Terminal Type: White lead Reliability Indicator: Not established Body Diameter: 1.250 inches Body Length: 1.312 inches Power Dissipation Rating In Watts: 1.251 free air Style Designator: 4xial terminals one end Test Data Document: 131349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	29.100 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0 to 145.0 Inclosure Method: Incapsulated Terminal Type: Wire Isad Reliability Indicator: Note established 30dy Diameter: 1.250 inches 30dy Diameter: 1.250 inches 30dy Length: 1.312 inches Power Dissipation Rating In Watts: 1.125 free air Style Designator: 24xial terminals one end Test Data Document: 31349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wie Unit Of Measure: - Demilitarization: No	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 notosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 2.250 inches Body Length: 2.312 inches Power Dissipation Rating In Watts: 2.125 free air Style Designator: Avalia terminals one end Test Data Document: 31349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wie Uputio Of Measure: - Demilitarization: No	-0.500 to 0.500
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Inclosure Method: Increminal Type: Mire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 2.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Unit Of Measure: — Demilitarization: No	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avail terminals one end Test Data Document: 31349-millip3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avail terminals one end Fest Data Document: 31349-milip3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization: No	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.315 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	-65.0 to 145.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Encapsulated
Reliability Indicator: Note established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type:
Note stablished Body Diameter: D.250 inches Body Length: D.312 inches Power Dissipation Rating In Watts: D.125 free air Style Designator: Axial terminals one end Test Data Document: B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Wire lead
Body Length: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Reliability Indicator:
Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Not established
Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.250 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Test Data Document: 31349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization: No	Body Length:
On 125 free air Style Designator: Axial terminals one end Test Data Document: B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	0.312 inches
Axial terminals one end Test Data Document: B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	0.125 free air
Test Data Document: 31349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:
B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Axial terminals one end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
V/a Unit Of Measure: Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
-11	No
-ng:	Fiig:
A001a0	A001a0