## NSN 5905-00-124-5026

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-124-5026

-20.0/+20.0  Electrical Resistance:  44.230 kilohms  Resistance Tolerance In Percent:  -0.100 to 0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established
44.230 kilohms  Resistance Tolerance In Percent: -0.100 to 0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0  Inclosure Method: Encapsulated Terminal Type: Wire lead  Reliability Indicator:
Resistance Tolerance In Percent: -0.100 to 0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
-0.100 to 0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0 to 145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
-65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:
Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:
Terminal Type: Wire lead Reliability Indicator:
Wire lead  Reliability Indicator:
Reliability Indicator:
Not established
Body Diameter:
0.250 inches
Body Length:
0.312 inches
Power Dissipation Rating In Watts:
0.125 free air
Style Designator:
Axial terminals one end
Test Data Document:
81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A001a0