NSN 5905-00-125-1023

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-125-1023

Electrical Resistance: 254.200 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wive lead Reliability Indicator: Not established Body Diameter: -0.375 inches Body Longth: -0.500 inches Power Dissipation Rating In Watts: -0.250 free air Style Designator: Avaital terminals one end Test Data Document: -0.345-milrg3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -0.109/-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	-20.0/+20.0
Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milit93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.520 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.): Shelf Life: N/A Unit Of Measure:	254.200 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 145.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milit93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-mill93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.375 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 10.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milir93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: Bai349-milip3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0 to 145.0 16closure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.375 inches Body Length: 10.500 inches Power Dissipation Rating In Watts: 10.500 inches Power Dissipation Rating In Watts: 10.500 inches Style Designator: Axial terminals one end Test Data Document: 181349-milir93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	-65.0 to 145.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Terminal Type:
Note established Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Wire lead
Body Diameter: 0.375 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Not established
Body Length: 0.500 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Body Diameter:
D.500 inches Power Dissipation Rating In Watts: D.250 free air Style Designator: Axial terminals one end Test Data Document: B1349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.375 inches
Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Body Length:
O.250 free air Style Designator: Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.500 inches
Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminals one end Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.250 free air
Test Data Document: 81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Style Designator:
81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Axial terminals one end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	81349-milr93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: 	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0