NSN 5905-00-125-1057

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-125-1057 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.9688 inches Pilot Length: 0.0620 inches First Flat Length: 0.440 inches Flat Height: 0.105 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 1.075 inches **Shaft Diameter:** Between 0.1242 inches and 0.1247 inches **Shaft Length:** 0.500 inches **Body Length:** 1.686 inches **Mounting Lip Diameter:** 1.0620 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:**

97.00 inch-ounces

Maximum Running Torque:
97.00 inch-ounces

NSN 5905-00-125-1057

Shelf Life:

N/a

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately delicate
End Application:
Aircraft, phantom f-4
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms 1st section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
5.0 free air all sections
Function Conformity Per Section:
All sections absolute conformity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections equation
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Test Data Document:
97942-577r900 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 turret

NSN 5905-00-125-1057

Precision Nonwire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A002a0