

View Online at <https://aerobasegroup.com/nsn/5905-00-125-1057>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.9688 inches

Pilot Length:

0.0620 inches

First Flat Length:

0.440 inches

Flat Height:

0.105 inches

Undercut Diameter:

0.975 inches

Undercut Width:

0.0570 inches

Body Diameter:

1.075 inches

Shaft Diameter:

Between 0.1242 inches and 0.1247 inches

Shaft Length:

0.500 inches

Body Length:

1.686 inches

Mounting Lip Diameter:

1.0620 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

97.00 inch-ounces

Maximum Running Torque:

97.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.001 inches

Fragility Factor:

Moderately delicate

End Application:

Aircraft, phantom f-4

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms 1st section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

5.0 free air all sections

Function Conformity Per Section:

All sections absolute conformity

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections equation

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Test Data Document:

97942-577r900 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0