

View Online at <https://aerobasegroup.com/nsn/5905-00-126-1553>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7495 inches and 0.7500 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Overall Length:

3.719 inches

Undercut Diameter:

0.750 inches

Undercut Width:

0.0570 inches

Body Diameter:

Between 0.870 inches and 0.880 inches

Shaft Diameter:

Between 0.124 inches and 0.125 inches

Shaft Length:

0.630 inches

Body Length:

3.063 inches

Overall Diameter:

1.096 inches

Mounting Lip Diameter:

Between 0.8700 inches and 0.8800 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0670 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3100.0 and 4100.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

10.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Power Dissipation Rating Per Section In Watts:

5.0 free air all sections

Fixed Tap Quantity Per Section:

1 all sections

Resistance Tolerance Per Section In Percent:

-1.0 to 1.0 1st section

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

5000.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0