Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-126-1737

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

1.406 inches

#### **Body Diameter:**

1.156 inches

Shaft Length:

0.781 inches

Mounting Bushing Length:

0.406 inches

### Body Length:

#### 0.625 inches

**Overall Diameter:** 

1.584 inches

Shaft Style:

Round

Actuator Type:

Single shaft

### Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Locking bushing

#### **Electrical Resistance Per Section:**

250.0 kilohms single section

#### **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

## Standard Taper Curve Per Section:

A single section

## **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0