

View Online at <https://aerobasegroup.com/nsn/5905-00-130-9030>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

Between 0.560 inches and 0.590 inches

Overall Height:

Between 0.510 inches and 0.530 inches

Overall Width:

Between 0.180 inches and 0.190 inches

Mounting Slot Width:

Between 0.020 inches and 0.030 inches

Shaft Diameter:

Between 0.090 inches and 0.100 inches

Shaft Length:

Between 0.034 inches and 0.036 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.180 inches and 0.190 inches

Body Height:

Between 0.510 inches and 0.530 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

Between 0.510 inches and 0.530 inches

Mounting Facility Quantity:

2

Terminal Location:

Upper adjacent side two rows

Mounting Method:

Slot

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

200.0 ohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0