Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-131-5805

# Section Quantity:

1

Body Style:

Cylindrical

## Reliability Indicator:

Not established

## Terminal Length:

0.188 inches

#### **Body Diameter:**

0.300 inches

#### Body Length:

0.250 inches

## **Overall Diameter:**

0.300 inches

## Actuator Type:

Flush drive with slot-hole

## Maximum Starting Torque:

3.00 inch-ounces

## Maximum Running Torque:

3.00 inch-ounces

## Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

## **Mounting Method:**

Terminal

## **Electrical Resistance Per Section:**

25.0 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

1440.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

## Actuator Travel Control Feature:

Clutch



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0