NSN 5905-00-132-0142

Section Quantity:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-132-0142

| 1 |
|--|
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| Between 1.796 inches and 1.828 inches |
| Shaft Diameter: |
| Between 0.2494 inches and 0.2497 inches |
| Shaft Length: |
| Between 0.781 inches and 0.843 inches |
| Mounting Bushing Length: |
| 0.375 inches |
| Body Length: |
| Between 1.719 inches and 1.781 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| Between 3600.0 and 3604.0 |
| Maximum Starting Torque: |
| 2.00 inch-ounces |
| Maximum Running Torque: |
| 2.00 inch-ounces |
| Maximum Stop Torque: |
| 550.00 inch-ounces |
| Nonturn Device Location: |
| At 6 oclock |
| Nonturn Device Radius: |
| Between 0.546 inches and 0.578 inches |
| Shaft End Play: |
| 0.005 inches |
| Shaft Runout: |
| 0.002 inches |
| Lateral Runout: |
| 0.005 inches |
| Pilot Diameter Runout: |
| 0.002 inches |
| |
| Shaft Radial Play: |

NSN 5905-00-132-0142

Precision Wire Wound Variable Resistor - Page 2 of 2



| Screw Thread Diameter: |
|--|
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 3600.0 and 3604.0 |
| Function Conformity Tolerance Per Section: |
| -0.15/+0.15 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 105.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 5.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -3.0 to 3.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Function Characteristic Per Section: |
| Single section linear |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |