## NSN 5905-00-132-0142

**Section Quantity:** 

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-132-0142

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
Between 1.796 inches and 1.828 inches
Shaft Diameter:
Between 0.2494 inches and 0.2497 inches
Shaft Length:
Between 0.781 inches and 0.843 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 1.719 inches and 1.781 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 3604.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
2.00 inch-ounces
Maximum Stop Torque:
550.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
Between 0.546 inches and 0.578 inches
Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:

## NSN 5905-00-132-0142

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3604.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0 to 3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0