NSN 5905-00-132-4365

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-132-4365

View Online at https://aerobasegroup.com/nsn/5905-00-132-4
Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
Between 0.525 inches and 0.545 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
Between 0.182 inches and 0.197 inches
Mounting Hole Diameter:
0.090 inches
Shaft Diameter:
Between 0.058 inches and 0.098 inches
Shaft Length:
Between 0.025 inches and 0.045 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.182 inches and 0.197 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
Between 0.513 inches and 0.526 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0

Between 7200.0 and 16200.0

NSN 5905-00-132-4365

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Test Data Document:
81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 wire lead
Specification Data:
81349-mil-r-22097/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: