NSN 5905-00-132-4367

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-132-4367 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.535 inches **Terminal Length:** 6.000 inches **Overall Height:** 0.500 inches **Overall Width:** 0.187 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.078 inches **Shaft Length:** 0.035 inches **Body Length:** 0.500 inches **Body Width:** 0.187 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 7200.0 and 16200.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity:**

Terminal Location:Rear end

NSN 5905-00-132-4367

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method: Unthreaded hole Electrical Resistance Per Section:	
Electrical Resistance Per Section:	
500.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
Between 7200.0 and 16200.0	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
150.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-250.0 to 250.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
85.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific	cation
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	n
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
3 wire lead	
Specification Data:	
81349-mil-r-22097/3 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	