Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-134-0424

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.56200 inches

Pilot Length:

0.06200 inches

Overall Length:

1.727 inches

Undercut Diameter:

1.750 inches

Undercut Width:

0.07800 inches

Body Diameter:

1.767 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.750 inches

Body Length:

0.977 inches

Overall Diameter:

2.120 inches

Mounting Lip Diameter:

1.76700 inches

Mounting Lip Depth:

0.09300 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 165.0 and 175.0

Terminal Location:

Upper adjacent side two rows

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

NSN 5905-00-134-0424

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 8.5 kilohms single section Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: 180.0 single section **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -300.0 to 300.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -5.0 to 5.0 ohms single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Tap Location From Ccw Terminal Per Section In Ohms: 4250.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 20.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 80020-41297 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 4 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0