## NSN 5905-00-134-0426

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-134-0426

Section Quantity:
2
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.5620 inches
Pilot Length:
0.0620 inches
Overall Length:
2.230 inches
Undercut Diameter:
1.750 inches
Undercut Width:
0.0780 inches
Body Diameter:
1.767 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.562 inches
Body Length:
0.977 inches
Overall Diameter:
2.120 inches
Mounting Lip Diameter:
1.7670 inches
Mounting Lip Depth:
0.0930 inches
Shaft Style:
Round
Contact Arm Electrical Off Position:
Fully ccw-cw
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 165.0 and 175.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring

## NSN 5905-00-134-0426

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
3.5 kilohms 1st section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
35.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
300.0 to 300.0 all sections
Power Dissipation Rating Per Section In Watts:
4.0 free air all sections
Fixed Tap Quantity Per Section:
1 1st section
Tap Location Tolerance Per Section:
1.0 to 1.0 ohms 1st section
Resistance Tolerance Per Section In Percent:
5.0 to 5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
4250.0 1st section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 all sections
Standard Taper Curve Per Section:
A all sections
Test Data Document:
30020-41297 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0