## NSN 5905-00-134-9841

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-134-9841 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.232 inches **Body Diameter:** 1.156 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 0.232 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Maximum Running Torque:** 12.00 inch-ounces **Maximum Stop Torque:** 12.00 inch-ounces **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 

1.0 ohms single section

## NSN 5905-00-134-9841

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



∆mhiant '	Tamnuratura l	In Daa Caleiu	e Par Saction	At Zara Para	ent Rated Power:
	i cilipulatule i	ili Deg Gelsiu	3 1 61 06611011	AL ZOIO I CIU	enii Naicu i Owen.

150.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0