## NSN 5905-00-134-9855

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-134-9855

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
Between 0.697 inches and 0.752 inches
Terminal Length:
Between 0.177 inches and 0.197 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
Between 0.255 inches and 0.270 inches
Mounting Hole Diameter:
Between 0.090 inches and 0.096 inches
Shaft Diameter:
Between 0.073 inches and 0.093 inches
Shaft Length:
Between 0.025 inches and 0.045 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.255 inches and 0.270 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.513 inches and 0.526 inches
Mounting Facility Quantity:
2
Terminal Location:
Right adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:

2.000 kilohms single section

## NSN 5905-00-134-9855

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9360.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg: