NSN 5905-00-135-1508

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-135-1508

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.56200 inches
Pilot Length:
0.06000 inches
Overall Length:
1.765 inches
First Flat Length:
0.450 inches
Flat Height:
0.213 inches
Undercut Diameter:
1.625 inches
Undercut Width:
0.09300 inches
Body Diameter:
1.750 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.950 inches
Body Length:
0.755 inches
Overall Diameter:
2.000 inches
Mounting Lip Diameter:
1.75000 inches
Mounting Lip Depth:
0.09300 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:

200.0

NSN 5905-00-135-1508

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Maximum Starting Torque:
1.40 inch-ounces
Maximum Running Torque:
1.40 inch-ounces
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
100.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
95.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+0.0 single section
Function Conformity Per Section:
Single section zero based linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-5.0/+5.0 ohms single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
2500.0 single section
Function Characteristic Per Section:
Single section equation
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

No

NSN 5905-00-135-1508

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0