NSN 5905-00-136-8039

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-136-8039 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.3750 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.375 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** Between 0.0932 inches and 0.0937 inches **Shaft Length:** 0.370 inches **Body Length:** 0.785 inches **Mounting Lip Diameter:** 0.5000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 254.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring

Electrical Resistance Per Section:

10.000 kilohms all sections

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

0.0 all sections

NSN 5905-00-136-8039

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.01 to 0.01 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-5.0/+5.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 all sections
Special Features:
127 degrees to right and left of center tap
Test Data Document:
19315-1908926 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
8 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0