NSN 5905-00-137-0577

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-137-0577

Electrical Resistance: 32.500 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Immurature Range Of Tempurature Coefficient In Deg Ce
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: 10.109 inches Body Length: 10.250 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 10.001 Body Diameter: 10.109 inches Body Length: 10.250 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches
D.001 Body Diameter: D.109 inches Body Length: D.250 inches
Body Diameter: 0.109 inches Body Length: 0.250 inches
0.109 inches Body Length: 0.250 inches
Body Length: 0.250 inches
0.250 inches
Power Dissipation Rating In Watts:
0.100 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0