NSN 5905-00-137-0646

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-137-0646 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.8750 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.313 inches **Undercut Width:** 0.0780 inches **Body Diameter:** 1.438 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Body Length:** 0.880 inches **Mounting Lip Diameter:** 1.4380 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 340.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.35 inch-ounces **Shaft End Play:** 0.0045 inches

Shaft Runout: 0.003 inches

NSN 5905-00-137-0646

No

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-5.0/+0.0 -65 degrees celsius all sections and -5.0 to 10.0 25 degrees celsius all sections and +0.0/+3.0 150 degrees celsius all sections
Function Conformity Tolerance Per Section:
-0.50 to 0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
1.5 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5905-00-137-0646

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0