Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-137-1003

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.688 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.640 inches

## Mounting Bushing Length:

0.375 inches

#### Body Length:

# 2.250 inches

Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

270.0

#### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

5.0 megohms single section

#### **Rotary Actuator Travel In Angular Deg:**

300.0

### Resistance Tempurature Characteristic Range Per Section In Percent:

+0.0 to 9.0 -55 degrees celsius single section and +0.0 to 2.5 0 degrees celsius single section and -3.5 to 3.5 85 degrees celsius single

section and -5.5 to 5.5 105 degrees celsius single section and -7.0 to 7.0 120 degrees celsius single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section



#### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

#### Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0