Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-137-4460

Section	Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.150 inches

Shaft Diameter:

0.100 inches

Shaft Length:

0.125 inches

Body Length:

0.750 inches

Body Width:

0.160 inches

Body Height:

0.310 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7200.0

Center To Center Distance Between Terminals:

0.500 inches

Fragility Factor:

Moderately delicate

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Humidity proof

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

7200.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-100.0 to 100.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
-10.0 to 10.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Standard Taper Curve Per Section:	
A single section	
Precious Material And Location:	
Terminals gold	
Precious Material:	
Gold	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	