## NSN 5905-00-137-4512

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-137-4512

Electrical Resistance: 47.500 kilohms Resistance Tolerance In Percent: 1.1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Bedy Length: 0.375 inches Prower Dissipation Rating In Watts: 0.125 free air Syle Designator: Avaid terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili755182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+175.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:  0.1010 Body Diameter:  0.125 inches Body Length:  0.375 inches Power Dissipation Rating In Watts:  0.125 free air Style Designator:  Axial terminal each end Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+175.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:  0.010  Body Diameter:  0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+175.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:  10.010  Body Diameter: 10.125 inches Body Length: 10.375 inches Power Dissipation Rating In Watts: 10.125 free air  Style Designator: Axial terminal each end Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+175.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.010  Body Diameter:  0.125 inches  Body Length:  0.375 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Terminal Type:  Wire lead  Reliability Indicator:  Established  Reliability Failure Rate Level In Percent:  0.010  Body Diameter:  0.125 inches  Body Length:  0.375 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent: 0.010  Body Diameter: 0.125 inches  Body Length: 0.375 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminal each end  Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: B1349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Established  Reliability Failure Rate Level In Percent:  0.010  Body Diameter:  0.125 inches  Body Length:  0.375 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Reliability Failure Rate Level In Percent:  0.010  Body Diameter:  0.125 inches  Body Length:  0.375 inches  Power Dissipation Rating In Watts:  0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Diameter:  0.125 inches  Body Length: 0.375 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator: Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
0.125 inches  Body Length: 0.375 inches  Power Dissipation Rating In Watts: 0.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
D.375 inches  Power Dissipation Rating In Watts:  D.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
O.125 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Style Designator:  Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Axial terminal each end  Test Data Document:  81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0