## NSN 5905-00-137-4662

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-137-4662

Section Quantity:						
1						
Body Style:						
Cylindrical bushing mounted						
Reliability Indicator:						
Not established						
Body Diameter:						
0.875 inches						
Shaft Diameter:						
0.125 inches						
Shaft Length:						
1.500 inches						
Mounting Bushing Length:						
0.250 inches						
Body Length:						
0.688 inches						
Shaft Style:						
Round, slotted						
Actuator Type:						
Single shaft						
Effective Electrical Rotation In Deg Angular Rotation:						
300.0						
Fragility Factor:						
Moderately rugged						
Screw Thread Diameter:						
0.250 inches						
Screw Thread Series Designator:						
Unef						
Screw Thready Qty Per Inch (tpi):						
32.0						
Terminal Location:						
Radially positioned over less than half the circumference						
Mounting Method:						
Standard bushing						
Electrical Resistance Per Section:						
35.0 ohms single section						
Rotary Actuator Travel In Angular Deg:						
300.0						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
340.0 single section						
Power Dissipation Rating Per Section In Watts:						

12.5 free air single section

## NSN 5905-00-137-4662

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



R	esistance	<b>Tolerance</b>	Per 9	Section	In	Percent:
◥	esisiance	i olei alice	rei .	Section		reiteiit.

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A002a0