

View Online at https://aerobasegroup.com/nsn/5905-00-137-7209

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.170 inches

#### Shaft Diameter:

0.100 inches

- Shaft Length:
- 0.060 inches

Body Length:

#### 0.750 inches

Body Width:

## 0.190 inches

**Body Height:** 

0.250 inches

Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

5400.0

## **Center To Center Distance Between Terminals:**

0.500 inches

## **Terminal Location:**

Lower adjacent side two rows

## **Mounting Method:**

Terminal

# Center To Center Distance Between Terminal Rows:

0.100 inches

# **Electrical Resistance Per Section:**

50.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

5400.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# NSN 5905-00-137-7209 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.75 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A002a0