Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-137-8050

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## Body Diameter:

1.250 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.062 inches

#### Mounting Bushing Length:

0.375 inches

#### Shaft Style:

Round

#### Switch Type:

ownen

# Rotary

Switch Voltage Rating In Volts:

125.0

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 3 oclock and at 9 oclock

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

## Mounting Method:

Standard bushing

## Features Provided:

Switch

## **Electrical Resistance Per Section:**

5.000 kilohms single section

## Power Dissipation Rating Per Section In Watts:

4.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Switch Current Type And Rating In Amps:

3.000 ac

## Standard Taper Curve Per Section:

A single section

# NSN 5905-00-137-8050

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0