NSN 5905-00-137-8051

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-137-8051 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted First Flat Length: 0.562 inches Flat Height: 0.188 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.062 inches **Body Length:** 0.625 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Bearing Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): Radially positioned over less than half the circumference

32.0 **Terminal Location: Mounting Method:** Standard bushing **Features Provided:** Switch

NSN 5905-00-137-8051

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
5.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Switch Current Type And Rating In Amps:
5.000 ac
Standard Taper Curve Per Section:
A single section
Special Features:
Terminals positioned on rear
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0