Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-138-1057

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.375 inches

### Mounting Bushing Length:

0.250 inches

#### Body Length:

### 1.109 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

### Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

275.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

9000.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0 to 30.0 single section

### Power Dissipation Rating Per Section In Watts:

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

### **Actuator Travel Control Feature:**

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0