Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-138-3410

## Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

## **Terminal Length:**

0.300 inches

#### Shaft Diameter:

0.090 inches

#### Shaft Length:

0.040 inches

## Body Length:

0.375 inches

#### Body Width:

0.203 inches

# Body Height:

0.375 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

7200.0

## **Center To Center Distance Between Terminals:**

0.200 inches

## Fragility Factor:

Moderately delicate

## **Terminal Location:**

Lower adjacent side two rows

## **Mounting Method:**

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

## **Features Provided:**

Humidity proof

## **Electrical Resistance Per Section:**

200.0 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

7200.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0