NSN 5905-00-138-3411

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-138-3411

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.110 inches
Shaft Length:
0.070 inches
Body Length:
1.260 inches
Body Width:
0.200 inches
Body Height:
0.330 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7200.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
7200.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section

1.0 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-00-138-3411

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: