

View Online at <https://aerobasegroup.com/nsn/5905-00-138-4239>

**Section Quantity:**

3

**Shaft Bearing Type:**

Bearing

**Switch Type:**

Rotary

**Actuator Type:**

Dual concentric

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Maximum Starting Torque:**

6.00 inch-ounces

**Nonturn Device Radius:**

0.437 inches

**Shaft End Play:**

0.00300 inches

**Shaft Radial Play:**

0.001 inches

**Switch Contact Arrangement:**

Single pole, single throw, normally open, both positions maintained

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

10.000 kilohms 3rd section and 5.000 kilohms 2nd section and 1.000 kilohms 1st section

**Function Conformity Tolerance Per Section:**

-3.00/+3.00 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-250.0/+250.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 3rd section and -5.0/+5.0 2nd section and -1.0/+1.0 1st section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0