

View Online at <https://aerobasegroup.com/nsn/5905-00-138-4239>

Section Quantity:

3

Shaft Bearing Type:

Bearing

Switch Type:

Rotary

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Maximum Starting Torque:

6.00 inch-ounces

Nonturn Device Radius:

0.437 inches

Shaft End Play:

0.00300 inches

Shaft Radial Play:

0.001 inches

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.000 kilohms 3rd section and 5.000 kilohms 2nd section and 1.000 kilohms 1st section

Function Conformity Tolerance Per Section:

-3.00/+3.00 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 3rd section and -5.0/+5.0 2nd section and -1.0/+1.0 1st section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0