Non-wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-138-4241

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Overall Length:**

3.438 inches

### First Flat Length:

0.437 inches

#### Flat Height:

0.214 inches

### Body Diameter:

1.062 inches

#### Shaft Diameter:

0.250 inches

### Shaft Length:

1.125 inches

## Mounting Bushing Length:

0.375 inches

### Body Length:

1.875 inches

### **Overall Diameter:**

1.274 inches

### Shaft Style:

Round, flatted

#### Switch Type:

Rotary

### Switch Voltage Rating In Volts:

115.0

### Actuator Type:

Dual concentric

### Effective Electrical Rotation In Deg Angular Rotation:

320.0

## Maximum Starting Torque:

8.00 inch-ounces

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.437 inches

## Shaft End Play:

0.00300 inches

# Shaft Runout:

0.005 inches

Non-wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
6.0
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, double throw, three positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
1.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Switch Current Type And Rating In Amps:
2.000 ac/dc
Standard Taper Curve Per Section:
A single section
Special Features:
Second shaft 0.125 in. Nom dia, 1.563 in. Nom lg, 0.312 in. Nom flat lg, 0.094 in. Nom flat h
Terminal Type And Quantity:

3 tab, solder lug and 3 turret

Non-wire Wound Variable Resistor - Page 3 of 3



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0