NSN 5905-00-138-5088

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-138-5088

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
2.500 inches
Mounting Bushing Length:
0.313 inches
Body Length:
0.750 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Shaft End Play:
0.01000 inches
Shaft Runout:
0.003 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.00300 inches
Shaft Radial Play:
0.003 inches
End Application:
2spruance class dd (963), supply class aoe, emory s. Land class as, sirius class t-afs 8, austin ship class lpd-4 amphibious transport
docks, forrestal class cv, wasp class lhd, virginia class cgn (41), oliver perry class ffg, tarawa class lha
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:

Unef

NSN 5905-00-138-5088

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0