## NSN 5905-00-138-7030

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-138-7030 **Section Quantity: Body Style:** 

**Reliability Indicator:** Not established **Overall Length:** 

**Terminal Length:** 

Rectangular

0.297 inches

0.188 inches **Overall Height:** 0.250 inches

**Overall Width:** 0.485 inches

**Body Length:** 0.297 inches **Body Width:** 0.297 inches

**Body Height:** 0.250 inches

**Actuator Type:** Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:** 

300.0

**Maximum Starting Torque:** 

5.00 inch-ounces

**Maximum Running Torque:** 

0.10 inch-ounces

**Center To Center Distance Between Terminals:** 

0.200 inches

**Terminal Location:** 

Rear end

**Mounting Method:** 

**Terminal** 

**Electrical Resistance Per Section:** 

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

300.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## NSN 5905-00-138-7030

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: