NSN 5905-00-138-7241

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-138-7241

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 50.0 to 50.0 Electrical Resistance: 1.800 kilohms Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length:
Electrical Resistance: 1.800 kilohms Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
Perpurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0 to 105.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
15.0 to 105.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
Ferminal Type: Wire lead Reliability Indicator: Not established
Vire lead Reliability Indicator: Not established
Reliability Indicator: Not established
Not established
Terminal Length:
Between 1.375 inches and 1.625 inches
Body Diameter:
Between 0.079 inches and 0.109 inches
Body Length:
Between 0.293 inches and 0.333 inches
Power Dissipation Rating In Watts:
1.000 free air
Precious Material And Location:
Ferminal surfaces gold
Style Designator:
Axial terminal each end
Test Data Document:
92220-r071/004 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A001a0