

View Online at https://aerobasegroup.com/nsn/5905-00-138-7389

### Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-30.0 to 30.0

### **Electrical Resistance:**

2.370 kilohms

### **Resistance Tolerance In Percent:**

-1.000 to 1.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

### 25.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 275.0

### **Inclosure Method:**

Encased

### **Terminal Type:**

Tab, solder lug

## Reliability Indicator:

- . . . . . .

# Established

Reliability Failure Rate Level In Percent:

0.010

### **Terminal Length:**

0.438 inches

### Body Length:

Between 0.538 inches and 0.662 inches

### **Body Width:**

Between 0.272 inches and 0.396 inches

### **Body Height:**

Between 0.289 inches and 0.351 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.719 inches

### **Power Dissipation Rating In Watts:**

8.000 free air

### **Mounting Hole Size:**

0.125 inches

### Cubic Measure (non-core):

0.064 cubic inches

### **Unpackaged Unit Weight:**

3.0 grams

### Style Designator:

Axial terminal (s)

#### **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



**Specification Data:** 

81349-mil-r-39009/1 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0