# NSN 5905-00-139-1744

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-139-1744

Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.472 inches
Terminal Length:
0.172 inches
Overall Height:
0.250 inches
Overall Width:
0.165 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.050 inches
Body Length:
0.250 inches
Body Width:
0.165 inches
Body Height:
0.250 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
200.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section

# NSN 5905-00-139-1744

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



0.25 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

## **Standard Taper Curve Per Section:**

A single section

## **Test Data Document:**

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

3 pin

#### **Specification Data:**

81349-mil-r-22097/5 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0