## NSN 5905-00-139-2200

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-139-2200

Signature Resistance:  125.000 ohms  Resistance Tolerance In Percent:  1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  1.50.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  1.50.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  1.50.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  1.50.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1.50.10 10 275.0  Tempurature Range Of Tempurature	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/4-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 to 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 to 275.0 Tempurature Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Note established 3040 Diameter: 1.005 inches 3040 Longth: 1.0250 inches 2.040 free air 8 Ryle Designator: Axial terminal each end Feet Data Document: 1.04149-mil-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). 35.101 tof Measure: 36.101 Celsius Ambient School Celsius At Full Rated Power: 36.102 Celsius At Full Rated Power: 36.103 Celsius At Full Rated Power: 36.103 Celsius At Full Rated Power: 36.103 Celsius At Full Rated Power: 36.104 Celsius At Full Rated Power: 36.105 Celsius A	-30.0/+30.0
Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 15.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0 1275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0 1275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0 1275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0 1275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0 1275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0 1275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0 1275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 156.0 1275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1575.0 Tempurature Range Of Tempurature Coefficient in Deg C	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 to 275.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 10.085 inches 30dy Length: 10.250 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: xival terminal each end Test Data Document: 181349-mil-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit of Measure: - Demilitarization: No	825.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 275.0  Inclosure Method:  Incapsulated  Teminal Type:  Wire lead  Retliability Indicator:  Not established  380dy Diameter:  10.085 inches  380dy Length:  10.250 inches  280dy Length:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 to 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 57.0 t	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 275.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  1.0.055 inches  Body Length:  1.0.250 inches  Power Dissipation Rating In Watts:  1.0.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  191349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life:  Wa Julit Of Measure:  - Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 275.0  nclosure Method: Encapsulated  Ferminal Type: Wife lead  Reliability Indicator: Not established  Body Diameter: 0.085 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 1.000 free air  Rytyle Designator: Axial terminal each end  Fest Data Document: 11349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Juit of Measure: - Demilitarization: No	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0 to 275.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Note established  Body Diameter:  10.085 inches  20.085 inches  20.095 inches  20.095 inches  20.095 inches  20.095 inches  20.096 prissipation Rating In Watts:  10.000 free air  Style Designator:  10.11 kxial terminal each end  Test Data Document:  10.11 system of the specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; by accludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  10.00 inclosed in the specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  10.00 inclosed in the specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; by account of the specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.085 inches 30dy Length: 0.250 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Xxial terminal each end Fest Data Document: 81349-mill-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 0xxcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life:  V/a Jinit Of Measure:	275.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  Does inches  Body Length:  Does inches  Power Dissipation Rating In Watts:  Lood free air  Style Designator:  Exial terminal each end  Fest Data Document:  B1349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Va  Joint Of Measure:  Demilitarization:	-55.0 to 275.0
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  10.085 inches  Body Length:  10.250 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Exial terminal each end  Fest Data Document:  10.1149-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Joint Of Measure:  - Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Reliability Indicator: Not established Reliability Indicator: Not established Reliability Indicator: Notes Relia	Encapsulated
Reliability Indicator: Not established  Body Diameter: 0.085 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.000 free air  Style Designator: Axial terminal each end  Fest Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: - Demilitarization:	Terminal Type:
Note established  30 dy Diameter:	Wire lead
Body Length:  0.085 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 1.000 free air  Style Designator: Axial terminal each end  Fest Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Reliability Indicator:
3.005 inches 3.005 inches 3.005 inches 3.006 power Dissipation Rating In Watts: 3.000 free air 3	Not established
Body Length:  2.250 inches  Power Dissipation Rating In Watts:  2.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  2.31349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	0.085 inches
Power Dissipation Rating In Watts:  1.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  131349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: B1349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	0.250 inches
Axial terminal each end  Fest Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  31349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	1.000 free air
Fest Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  No  Demilitarization:	Style Designator:
B1349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:	81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Unit Of Measure: - Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a  Jnit Of Measure:  - Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization: No	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Filg:	No
	Fiig:
N001a0	A001a0