NSN 5905-00-139-3078

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-139-3078 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.495 mils and 0.505 centimeters **Shaft Diameter:** Between 0.1248 inches and 0.1251 inches **Shaft Length:** Between 0.690 inches and 0.710 inches **Mounting Bushing Length:** Between 0.297 inches and 0.327 inches **Body Length:** Between 0.300 inches and 0.310 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:** 12.00 inch-ounces **Maximum Running Torque:** 12.00 inch-ounces **Maximum Stop Torque:** 80.00 inch-ounces **Shaft End Play:** 0.006 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.003 inches **Pilot Diameter Runout:** 0.002 inches **Shaft Radial Play:**

0.003 inches **Fragility Factor:** Moderately rugged

NSN 5905-00-139-3078

Precision Wire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.060 cubic inches
Electrical Resistance Per Section:
50.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
330.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-139-3078

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0