

View Online at <https://aerobasegroup.com/nsn/5905-00-140-6130>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.922 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.375 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.375 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

150.0 ohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-25.0 to 25.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Resistance Tolerance Per Section In Percent:

-2.0 to 2.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

65.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0