NSN 5905-00-140-6150

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-140-6150 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Terminal Length:** 6.000 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches **Shaft Diameter:** Between 0.058 inches and 0.098 inches **Shaft Length:** Between 0.025 inches and 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** Between 0.182 inches and 0.197 inches **Body Height:** Between 0.490 inches and 0.510 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 7200.0 and 15120.0 **Lateral Distance Between Mounting Hole Centers:** Between 0.513 inches and 0.526 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Humidity proof **Cubic Measure:** 0.470 cubic inches

Electrical Resistance Per Section:

500.0 ohms single section

NSN 5905-00-140-6150

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator	Travel In Angular	Deg:
------------------------	-------------------	------

Between 7200.0 and 15120.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire lead

Specification Data:

81349-mil-r-39015/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0