NSN 5905-00-140-9608

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-140-9608

Section Quantity:
1
Body Style:
Cylindrical
Overall Length:
Between 0.418 inches and 0.656 inches
Terminal Length:
Between 0.250 inches and 0.375 inches
Body Diameter:
Between 0.240 inches and 0.260 inches
Shaft Diameter:
0.109 inches
Shaft Length:
0.085 inches
Body Length:
Between 0.218 inches and 0.281 inches
Overall Diameter:
Between 0.240 inches and 0.260 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
3.00 inch-ounces
Terminal Location:
Rear end
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
50.000 ohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-0.0 to 500.0 single section

0.5 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-00-140-9608

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: