NSN 5905-00-140-9743

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-140-9743

Rectrical Resistance: 00.000 ohms Resistance Tolerance In Percent: 1.000 to 1.000 Imbient Tempurature In Deg Celsius At Full Rated Power: 5.0 Imbient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Imbient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0 Inclosure Method: Incapsulated Ierminal Type: Iffice lead Ieliability Failure Rate Level In Percent: 1.00 Inclosure Method: Incapsulated Ieliability Failure Rate Level In Percent: 1.00 Inclosure Method: Incapsulated Ieliability Failure Rate Level In Percent: 1.00 Inclosure Method: Incapsulated Ieliability Failure Rate Level In Percent: 1.00 Inclosure Method: Incapsulated Ieliability Failure Rate Level In Percent: 1.00 Inclosure Method: Incapsulated Incomplete Inclosure Inclosure Method: Incapsulated Inclosure	Electrical Resistance: 300.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.6.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire laad Reliability Indicator: Established Reliability Fallure Rate Level In Percent: 0.187 inches Body Diameter: 0.187 inches Body Length: 0.580 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications. reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Na Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
tesistance Tolerance in Percent: 1,000 to 1,000 Imbient Tempurature in Deg Celsius At Full Rated Power: 5,0 Imbient Tempurature in Deg Celsius At Zero Percent Rated Power: 75,0 Imbient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55,0 to 275,0 Inclosure Method: Incapsulated	Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: -0.100 Body Diameter: -0.187 inches Body Length: -0.560 inches Power Dissipation Rating In Watts: -0.300 free air Style Designator:	-20.0/+20.0
resistance Tolerance In Percent: 1.000 to 1.000 Imbient Tempurature In Deg Celsius At Full Rated Power: 5.0 Imbient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0 Impurature Method: Impaculated Impurature Rate Level In Percent: Impu	Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -5.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Failure Rate Level in Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating in Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil+-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Na Unit Of Measure:	Electrical Resistance:
mbient Tempurature In Deg Celsius At Full Rated Power: 5.0 imbient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0 impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0 inclosure Method: incapsulated incapsulat	-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure:	300.000 ohms
Imbient Tempurature In Deg Celsius At Zero Percent Rated Power: 5.0 Imbient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Impurature Range Of Tempurature Coefficient in Deg Celsius: 5.5 to to 275.0 Inclosure Method: Incapsulated Impurature Range Of Tempurature Coefficient in Deg Celsius: 5.5 to to 275.0 Inclosure Method: Incapsulated Impurature In Deg Celsius At Zero Percent Rated Power: 5.5 to to 275.0 Inclosure Method: Incapsulated Impurature Method: Incapsulated Impurature Rate Level In Percent: Incology Diameter: Intology Diameter: Intology Diameter: Intology Diameter: Intology Length: Intology Diameter: Intology Length: Intology Diameter: Intolo	Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.187 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milk-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average*, "", etc.). Shelf Life: Na Unit Of Measure:	Resistance Tolerance In Percent:
imbient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 empurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0 inclosure Method: incapsulated erminal Type: Wire lead deliability Indicator: stabilished teliability Failure Rate Level In Percent: 100 iody Diameter: 187 inches iody Length: 550 inches over Dissipation Rating In Watts: 1000 free air tyte Designator: xial terminal each end test Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain nivironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). theff Life: We int Of Measure: termilitarization:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.1787 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure:	-1.000 to 1.000
Inhibient Tempurature In Deg Celsius At Zero Percent Rated Power: 75.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 65.0 to 275.0 Inclosure Method: Incapsulated Impurature Rate Level In Percent: Incapsulated	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
remurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0 iclosure Method: incapsulated derminal Type: Wire lead teliability Indicator: istablished teliability Failure Rate Level In Percent: .100 tody Diameter: .187 inches tody Length: .560 inches tower Dissipation Rating In Watts: .000 free air tyte Designator: xxial terminal each end est Data Document: 1349-mili-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification princt; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain princt Life: Use their Life: Use termilitarization:	Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5 to 27.5.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: Brianglian-raspoot/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	25.0
empurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 275.0 Inclosure Method: Incapsulated Incaps	Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: incapsulated erminal Type: Wire lead teliability Indicator: stabilished teliability Failure Rate Level In Percent: 1.00 tody Diameter: 1.187 inches tody Length: 1.560 inches tody Length: 1.560 inches tower Dissipation Rating In Watts: 1.000 free air type Designator: xial terminal each end test Data Document: 1.1849-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain formation of the commercial catalogs of the commercial cata	-5.0 to 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	275.0
Inclosure Method: Incapsulated	Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
reminal Type: Vire lead deliability Indicator: istablished teliability Failure Rate Level In Percent: 100 tody Diameter: 187 inches tody Length: 560 inches tower Dissipation Rating In Watts: 000 free air tiyle Designator: xial terminal each end est Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification primat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain nivironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). theff Life: I/a Init Of Measure: **Permilltarization:	Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-55.0 to 275.0
eminal Type: Vire lead deliability Indicator: stablished deliability Failure Rate Level In Percent: .100 dody Diameter: .187 inches dody Length: .560 inches dower Dissipation Rating In Watts: .000 free air style Designator: xial terminal each end dest Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification primat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain nivironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). thelf Life: Va Init Of Measure: demilitarization:	Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead teliability Indicator: stabilished teliability Failure Rate Level In Percent: .100 tody Diameter: .187 inches tody Length: .560 inches tower Dissipation Rating In Watts: .000 free air tyle Designator: .xial terminal each end test Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification tomat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). thelf Life: Va Init Of Measure: tentilitarization:	Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
teliability Indicator: stablished teliability Failure Rate Level In Percent:100 tody Diameter:187 inches tody Length:560 inches tower Dissipation Rating In Watts:000 free air tyle Designator: xial terminal each end test Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification tormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain novironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). the It Life: Ida Init Of Measure: tensilitarization:	Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
stablished teliability Failure Rate Level In Percent:100 tody Diameter:187 inches tody Length:560 inches tower Dissipation Rating In Watts:000 free air tyle Designator: xital terminal each end test Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain revironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). the It is the It i	Established Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
teliability Failure Rate Level In Percent: .100 lody Diameter: .187 inches .187 inches .188 inches .189 inches .1	Reliability Failure Rate Level In Percent: 0.100 Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
indody Diameter:187 inches dody Length:560 inches dower Dissipation Rating In Watts:000 free air ityle Designator:xial terminal each end dest Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). inhelf Life: Ma lift Of Measure: demilitarization:	Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Established
tody Diameter:187 inches tody Length:560 inches tower Dissipation Rating In Watts:000 free air tyle Designator:xial terminal each end test Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain novironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: We be the time of time of the time of the time of time of the time of time	Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Failure Rate Level In Percent:
And the state of t	0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.100
sody Length: .560 inches .560 inches .500 tree air .500 free air .501 besignator: .502 besignator: .503 besignator: .504 besignator: .505 and Document: .506 and Document: .507 and Document: .508 and Document: .509 and Docu	Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
cower Dissipation Rating In Watts: .000 free air Exyle Designator: .xial terminal each end Sest Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Ida Init Of Measure: Demilitarization:	O.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.187 inches
Tower Dissipation Rating In Watts: .000 free air ixtyle Designator: .xial terminal each end fest Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Init Of Measure: Demilitarization:	Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
cityle Designator: exial terminal each end fest Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: I/a I/a I/a I/a I/a I/a I/a I/	3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.560 inches
style Designator: xial terminal each end rest Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: I/a Init Of Measure:	Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
est Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: I/a Init Of Measure:	Axial terminal each end Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.000 free air
fest Data Document: 1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: I/a Init Of Measure: Demilitarization:	Test Data Document: 81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
1349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Unit Of Measure: Demilitarization:	81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain invironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: I/a Init Of Measure: Demilitarization:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: I/a Init Of Measure: Demilitarization:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-39007/11 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: I/a Init Of Measure: Demilitarization:	Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
l/a Init Of Measure: Demilitarization:	N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Init Of Measure: Demilitarization:	Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
emilitarization:	Demilitarization: No Fiig:	N/a
	No Fiig:	Unit Of Measure:
	No Fiig:	
lo	Fiig:	Demilitarization:
		No
iig:	A001a0	Fiig:
00100		A001a0