NSN 5905-00-143-7389

Section Quantity:

Cylindrical bushing mounted

Reliability Indicator:

Body Style:

2

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-143-7389

Not established
Body Diameter:
1.062 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.187 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Front-rear
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
250.0 kilohms all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 1st section
Standard Taper Curve Per Section:
A 1st section

NSN 5905-00-143-7389

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Termi	nal Type And	d Quantity:
6 tab,	solder lug	

o tab, solder id

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0